



Clad Plus 2 Exterior Door Frame 20 Year Limited Warranty

All Clad Plus 2 Exterior Door Frames, hereafter referred to as "products" sold by Young Manufacturing Company, Incorporated, hereafter referred to as the "Company," are subject to this Clad Plus 2 Exterior Door Frame 20 Year Limited Warranty, hereafter referred to as "this 20 Year Limited Warranty."

20 Year Limited Warranty

The Company warrants that its products, if properly stored, transported, used, and installed according to the enclosed Care and Finishing Instructions, will be free of defects in material and workmanship and free of rot and decay for 20 years from the date of original installation.

If the Company product that is the subject of this 20 Year Limited Warranty fails during the warranty period for reasons covered by this 20-Year Limited Warranty and the purchaser submits the written service request required under this 20 year Limited Warranty, the Company will replace the product with a product that is functionally at least equal to the product being replaced.

Extent of 20 Year Limited Warranty

This 20 Year Limited Warranty does not cover damages due to external causes, including, but not limited to, accidents, misuse, neglect, alteration, repair, or improper installation or maintenance.

Care and Finishing Instructions are available through your Young Manufacturing Company, Inc. distributor. Any use or care not in accordance with these Care and Finishing Instructions voids this 20 Year Limited Warranty, and any damage caused by such use or care is not covered under this 20 Year Limited Warranty.

This 20 Year Limited Warranty is limited to the original purchaser and is not transferable.

Warranty Service

To obtain warranty service, the purchaser must submit a written service request to the Company at Young Manufacturing Company, Incorporated, PO Box 167, Beaver Dam, KY 42320. A written service request must include original proof of purchase that must show the date of purchase, and an explanation of the problem.

Warranty Limitations and Exclusions

This warranty replaces all other warranties, express or implied, including, but not limited to, the implied warranties of merchantability and Fitness for a particular purpose. The Company makes no express warranty beyond that stated here. The Company disclaims all other warranties, express or implied, including, without limitation, implied warranties of merchantability and fitness for a particular purpose. No salesman, dealers, distributor, agent, employee, or representative of the company has the authority to change the terms of this warranty.

Some laws do not allow the exclusion of implied warranties, so this limitation may not apply to you. If these laws apply, all express and implied warranties are limited in duration to the limited warranty period. No warranties apply after that period. Some laws do not allow limitations on how long an implied warranty lasts, so this limitation may not apply to you.

The use of any sample or model during the negotiations leading to the purchase of the product serves merely to indicate a type of product that will be tendered to the purchaser. These samples or models create no warranty that the product will conform to the sample or models.

Limitations of Liability

The Company's responsibility under this or any other warranty, implied or expressed, is limited to replacement of the product at no charge, and associated labor costs not exceeding \$100, as set forth previously. This remedy is the sole and exclusive remedy for any breach or warranty. The Company is not responsible for labor costs, indirect, special, incidental, or consequential damages resulting from any breach of warranty or under any other legal theory, including, but not limited to, lost profits, downtime, and any damage to or replacement of equipment and property. Some jurisdictions do not allow the exclusion or limitation of incidental or consequential damages, so the above limitations or exclusions may not apply to you. This 20 Year Limited Warranty gives you specific legal rights, and you may also have other rights that vary from jurisdiction to jurisdiction.



Clad Plus 2 Exterior Door Frame 20 Year Limited Warranty

Care and Installation Instructions

1. The jambs, brick mould, mull casing, and mull posts must not be cut, trimmed, or remachined in any way (except to route for hinges and lock).
2. Store in a clean and dry area: not in damp, moist, or extremely humid environments. Wood is hygroscopic and dimensionally influenced by changes in moisture content caused by its surrounding environment.
3. Door units should be lifted and carried when being moved: not dragged.
4. The rough opening should be no more than 1 1/2" wider and no more than 1" higher than the outside dimensions of the door system frame (jamb). The rough opening should be no more than 1/8" out of plumb over the height of this opening. The subsill (the bottommost horizontal structural member of the rough opening) should be capable of being leveled to within +1/16" over the width of the opening, but not sloped to the interior of the home.
5. Apply mastic or sealant to the rough opening as required. Particular attention should be paid to forming a positive seal beneath the sill or threshold.
6. Locate the frame of the door system within the rough opening and shim so that the frame is plumb, square, and level. Particular attention should be paid to shimming behind the lockstrike and hinge areas of the frame. **UNIT MUST BE INSERTED COMPLETELY INTO OPENING.** Check clearance between door and head jamb. It should be a uniform space approximately 1/8". If space at the top of the lock side is too great, shim under hinge jamb to raise door so that clearance is uniform across top of door. When installing sidelite, patio or twin units, shims may be necessary under center of sill or under mull post to prevent sagging if floor is uneven.
7. **PLUMB HINGE JAMB** Level or plumb the hinge jamb on the face and edge before fastening with jamb jack. Temporary shims may be needed between the brick mould and sheathing if wall is not plumb.
8. **INSTALLATION USING JAMB JACKS** Start 3" jamb jack screw into bottom jamb jack insert on hinges side. Turn screw clockwise using TORX Screwdriver until screw snaps in place (must snap twice). Repeat this procedure with top hinge side jamb jack. Next, place level on face of jamb and plumb by adjusting top and bottom jamb jack (turn clockwise to pull jamb to stud: counter clockwise to push away from stud). Insert screws into center jacks and adjust space between door and jamb by turning either clockwise or counter clockwise. **TO SECURE LOCK JAMB** Adjust head clearance, if needed, with shim under lock jamb and repeat hinge side procedure. Solid shims are recommended behind strike plate locations. After unit is fully installed, cover jamb jack holes with finishing caps.
9. Do not secure unit through exterior trim (brick mould).
10. Install flashing at the head, jambs, and sill as required to preclude penetration of water into the wall cavity. Seal all joints between the frame of the door system and the rough opening. Fill all gaps of 1/4" or more with backup or filler materials such as foam or fibrous insulation. Use only sealants recommended by the manufacturer for the intended application and apply in accordance with the sealant manufacturer's installation instructions. Make sure brick mould is sealed to sheathing.
11. **INTERIOR of Clad Plus 2 Frames is Primed Only:** It should be finished with acrylic top coat within 30 days of installation. Follow paint manufacturers instructions.
12. Do Not Paint Weatherstrip.
13. Clad Plus II should be kept clean of buildup of dirt and debris with fresh water and mild detergent.